



MHM IMPORT - EXPORT AND PRODUCTION COMPANY LIMITED

Tel: (+84) 703 708 999

Website: <https://mhmcoatings.com/>

Address: No. 9, Lane 28/76 Xuan La Street, Tay Ho District, Hanoi City, Vietnam

Factory: Thuan Thanh 3 Industrial Park, Thanh Khuong District, Bac Ninh Province, Vietnam

TECHNICAL DATA SHEET

MAXEFFORT M90

PRODUCT NAME : UNDERCOAT MAXEFFORT M90 - WATER BASE
PRODUCT CODE : MAXEFFORT M90
COLOR : BLACK
SHELF LIFE : 12 MONTH
MANUFACTURER : MHM IMPORT - EXPORT AND PRODUCTION COMPANY LIMITED

PRODUCT DESCRIPTION:

- The product creates a flexible, fast-drying coating for the metal parts underneath the car (chassis and fenders) to prevent kickbacks and rust
- High adhesive and soundproofing properties for the car
- Can be painted directly on the surface.
- The effect of paint depends on how to this work is done

INGREDIENTS:

Resin, pigments, additives...

TYPICAL PROPERTIES:

Mixed Ratio (by weight)	: Spray directly (stir well before use)
Solid Content (%)	: $50\% \pm 0.3$
Specific Gravity (25°C)	: 1.02 ± 0.05
Storage	: 36 months during 10°C to 30°C
Film Thickness	: 150 – 200 μm
Humidity	: 55 – 80%

APPLICATION METHODS:

Roller, Spray Gun

SAFETY:

Refer to Safety Data Sheet before handling or use.

APPLICATIONS DATA:

(1) Spray Method	Film Thickness	150 – 200 µm
	Dry to touch	10-20 min
	Dry to handle	1.5 - 2 hrs
	Ratio mixing	spray directly
	Spray Equipment	undercoat spray gun
	Spray gun pressure	40 - 50 psi (4-6 bars)
	Number of coats	2 coats
(2) Safety, Healthy	Flammable Liquid	Do not expose to heat, sparks or open flame.
	Skin Contact	May cause moderate skin irritation. Avoid prolong contact with skin. Use solvent resistant glove. To remove splashes of paint from skin, use soap and water.
	Eye Contact	Cause severe eye irritation and blurred vision. Safety glasses / goggles with side shields recommended. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
	Inhalation	Respiratory irritation. Only used in well ventilated areas. Do not breathe vapor or spray paint. Respirator with organic vapor cartridges recommended.

NOTE:

The information given applies to the product and its performance under specific test conditions. Due to the varied circumstances beyond our control under which the product may be applied, for specific applications, please contact MHM technical.